

## MONO-FACIAL MODULE

# RS6-570~595N-E3





N-Type /Positive power tolerance of 0~+3%/Max module efficiency 23.03%

- Suitable for ground power plants and distributed projects
- Advanced module technology delivers superior module efficiency
  - Non destructive cutting · MBB half-cut
- Excellent power generation performance
  - Excellent IAM and low irradiation performance · Lower temperature coefficient
  - 0.40% linear Power decline
- High module quality ensures long-term reliability
  - Strict selected material · Advanced technology · Leading standard
- Ultra-hydrophilic self-cleaning coating techniques
- Enhanced Mechanical Load
  - Mechanical performance up to 5400pa positive load and 2400pa negative load

Complete System  
and IEC Product Certification

IEC 61215(2016), IEC 61730(2016) ISO9001:  
2015:Quality Management System ISO14001:  
2015:Environment Management System  
ISO45001:2018:Occupational Health  
and Safety Management System




30-Year Excess Linear Power Output Warranty





# RS6-570~595N-E3

MONO-FACIAL MODULE



Drawing Only for Reference



| Electrical Characteristics STC | RS6-570N-E3 | RS6-575N-E3 | RS6-580N-E3 | RS6-585N-E3 | RS6-590N-E3 | RS6-595N-E3 |
|--------------------------------|-------------|-------------|-------------|-------------|-------------|-------------|
| Maximum Power (Pmax)           | 570W        | 575W        | 580W        | 585W        | 590W        | 595W        |
| Power Tolerance                | 0~+5W       | 0~+5W       | 0~+5W       | 0~+5W       | 0~+5W       | 0~+5W       |
| Module Efficiency              | 22.07%      | 22.26%      | 22.45%      | 22.65%      | 22.84%      | 23.03%      |
| Maximum Power Current (Imp)    | 13.26A      | 13.32A      | 13.38A      | 13.44A      | 13.50A      | 13.56A      |
| Maximum Power Voltage (Vmp)    | 42.99V      | 43.17V      | 43.35V      | 43.53V      | 43.70V      | 43.88V      |
| Short Circuit Current (Isc)    | 13.89A      | 13.95A      | 14.01A      | 14.07A      | 14.13A      | 14.19A      |
| Open Circuit Voltage (Voc)     | 52.39V      | 52.59V      | 52.79V      | 52.99V      | 53.19V      | 53.39V      |

Values at Standard Test Conditions STC(AM1.5, Irradiance 1000W/m<sup>2</sup>, Cell Temperature 25°C)

| Electrical Characteristics NOCT | RS6-570N-E3 | RS6-575N-E3 | RS6-580N-E3 | RS6-585N-E3 | RS6-590N-E3 | RS6-595N-E3 |
|---------------------------------|-------------|-------------|-------------|-------------|-------------|-------------|
| Maximum Power (Pmax)            | 432W        | 436W        | 440W        | 444W        | 448W        | 452W        |
| Maximum Power Current (Imp)     | 10.65A      | 10.70A      | 10.75A      | 10.80A      | 10.85A      | 10.90A      |
| Maximum Power Voltage (Vmp)     | 40.56V      | 40.75V      | 40.93V      | 41.11V      | 41.29V      | 41.47V      |
| Short Circuit Current (Isc)     | 11.28A      | 11.33A      | 11.38A      | 11.43A      | 11.48A      | 11.53A      |
| Open Circuit Voltage (Voc)      | 49.29V      | 49.53V      | 49.76V      | 49.99V      | 50.22V      | 50.45V      |

NOCT, Irradiance of 800W/m<sup>2</sup>, AM1.5, Ambient Temperature 20 °C, wind Speed 1m/s.

## Mechanical Characteristics

|              |                                                 |
|--------------|-------------------------------------------------|
| Cell Type    | Mono N-Type,144(6×24) Half-Cut cells            |
| Glass        | 3.2mm,High Transmission,Low Iron,tempered glass |
| Frame        | Anodized Aluminum Alloy                         |
| Junction Box | IP68 Rated                                      |
| Dimension    | 2278x1134x30mm                                  |
| Output Cable | 4mm2(EU),300mm,length can be customized         |
| Weight       | 27kg                                            |
| Connector    | MC4 Compatible                                  |

## Packing Information

|                       |        |
|-----------------------|--------|
| Container             | 40' HQ |
| Pallets per Container | 20     |
| Pieces per Container  | 740    |

## Characteristics

|                                          |             |
|------------------------------------------|-------------|
| Temperature Coefficient of Voc           | -0.25%/°C   |
| Temperature Coefficient of Isc           | +0.045%/°C  |
| Temperature Coefficient of Pmax          | -0.29%/°C   |
| Nominal Operating Cell Temperature(NOCT) | 43±2°C      |
| Fire Performance                         | IEC Class C |

Remark:Electrical data in this catalog do not refer to a single module and they are not part of the offer.They only serve for comparison among different module types.

## Maximum Ratings

|                            |             |
|----------------------------|-------------|
| Operating Temperature      | -40°C~+85°C |
| Maximum System Voltage     | 1500VDC     |
| Maximum Series Fuse Rating | 25A         |

